



P&WC

# SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

Version : 1.1  
Date of preparation : 15 January 2018  
Previous date : 09 January 2014

### 1. Chemical product and company identification

**Product name** SPEC-AID 8Q5001 (FuelAid ULS 500)

**Synonyms** Not available.

#### Recommended use and Limitations on use

**Recommended use** Cold flow improver

**Issue date** Jan-09-2014

**Revision date** 15/01/2018

**Supersedes date** 09/01/2014

#### Company/undertaking identification

JV Process and Water Chemicals LLC

Address: Street V. Kadirov 10, Chirchik city,  
Tashkent Region, Republic of Uzbekistan, 111727

Tel: +99871 209 10 40

Email address: info@pwch.uz

www.pwch.uz

### 2. Hazards identification

#### Emergency overview

May be ignited by heat, sparks or flames. May cause damage to organs. May cause drowsiness and dizziness. Suspected of causing cancer. Causes serious eye irritation. Causes skin irritation. May cause irritation to the respiratory system. May cause an allergic skin reaction. Prolonged exposure may cause chronic effects.

#### Hazard categories

##### Physical hazards

Flammable liquids Category 4

##### Health hazards

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Sensitization, skin Category 1

Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated exposure Category 2

##### Environmental hazards

Not classified.

#### Label elements

##### Pictograms



##### Signal word

Warning

##### Hazard statement

H227 Combustible liquid.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.



# P&WC SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

### Precautionary statement

#### Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from flames and hot surfaces. No smoking.
P210	Keep away from flames and hot surfaces-No smoking.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P321	Specific treatment (see this label).
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.

#### Storage

P235	Keep cool.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

#### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	-----------------------------------------------------------------------------------------------------

**Physical and chemical hazards** Combustible liquid. The product is stable and non-reactive under normal conditions of use, storage and transport.

**Health hazards** May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful. Causes skin irritation. May cause an allergic skin reaction. Expected to be a low ingestion hazard. Causes serious eye irritation.

**Environmental hazards** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Supplemental information** None.

### 3. Composition/information on ingredients

Substance/mixture	Mixtures	
Chemical name	Concentration (%)	CAS Number
Solvent naphtha (petroleum),heavy aromatic	30 - 60	64742-94-5
1,2,4-Trimethylbenzene	<= 10	95-63-6
Naphthalene	<= 10	91-20-3

### 4. First aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.



P&WC

# SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

Version : 1.1

Date of preparation : 15 January 2018

Previous date : 09 January 2014

<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms and health effects</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
<b>Expected acute symptoms and delayed symptoms</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
<b>Personal protection for first-aid responders</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
<b>Notes to physician</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
 <b>5. Fire-fighting measures</b>	
<b>Extinguishing media</b>	Water fog.
<b>Extinguishing media to avoid</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards</b>	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
<b>Special fire fighting procedures</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Protection of fire-fighters</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>General fire hazards</b>	Combustible liquid.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
 <b>6. Accidental release measures</b>	
<b>Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>For emergency responders</b>	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>Clean-up methods and materials and containment measures</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
<b>Recovery and neutralization</b>	Not available.
<b>Prevention of secondary hazards</b>	Not available.



P&amp;WC

# SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

### 7. Handling and storage

**Handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

**Storage**

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

**Exposure limits**

China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007)

Components	Type	Value
Naphthalene (CAS 91-20-3)	PC-STEL	75 mg/m <sup>3</sup>
	PC-TWA	50 mg/m <sup>3</sup>

**Biological limit values**

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Naphthalene (CAS 91-20-3)	2.5 µg/l	1-Hydroxypyrene, with hydrolysis (1-HP)	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

China OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Chemical Hazardous Agents (GBZ 2.1-2007): Skin designation

NAPHTHALENE (CAS 91-20-3)

Can be absorbed through the skin.

**Monitoring methods**

Follow standard monitoring procedures.

**Engineering measures**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

**Personal protective equipment****Respiratory protection**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

**Hand protection**

Wear appropriate chemical resistant gloves.

**Eye protection**

Wear safety glasses with side shields (or goggles).

**Skin and body protection**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Hygiene measures**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

### 9. Physical and chemical properties

**Appearance**

Liquid

**Physical state**

Not available.

**Form**

Liquid.

**Color**

Colorless to light yellow



P&amp;WC

# SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

Version : 1.1

Date of preparation : 15 January 2018

Previous date : 09 January 2014

Odor	Slight hydrocarbon
Melting point/freezing point	4 °C
Boiling point, initial boiling point, and boiling range	177 °C
Flash point	68 °C P-M(CC)
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 5 mm Hg
Vapor pressure temp.	21 °C
Vapor density	> 1 (Air = 1)
Relative density	0.91
Relative density temperature	21 °C
Density	Not available.
Solubility(ies)	
Solubility (water)	< 0.01 %
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Evaporation rate	< 1 (Ether = 1)
Other data	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Pour point	7 °C
Specific gravity	0.908
Viscosity temperature	21 °C
VOC (Weight %)	50 % (Estimated)

### 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Stability	Not available.
Possibility of hazardous reactions	Not available.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

### 11. Toxicological information

#### Acute toxicity

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 3160 mg/kg
<i>Inhalation</i>		
LC50	Rat	18 mg/L, 4 Hour



P&amp;WC

# SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

Version : 1.1

Date of preparation : 15 January 2018

Previous date : 09 January 2014

Components	Species	Test Results
<i>Oral</i> LD50	Rat	5000 mg/kg
Naphthalene (CAS 91-20-3)		
<b>Acute</b> <i>Dermal</i> LD50	Rabbit	> 16000 mg/kg
<i>Oral</i> LD50	Rat	> 2000 mg/kg
Solvent naphtha (petroleum), heavy aromatic (CAS 64742-94-5)		
<b>Acute</b> <i>Dermal</i> LD50	Rabbit	> 3160 mg/kg
<i>Inhalation</i> LC50	Rat	> 5.2 mg/L, 4 Hour
<i>Oral</i> LD50	Rat	7050 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Routes of exposure</b>	Inhalation. Skin contact. Eye contact.
<b>Symptoms</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer. This product is not expected to cause respiratory sensitization.
<b>Skin sensitizer</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>China OELs for hazardous agents in the workplace: Carcinogen Category</b>	
NAPHTHALENE (CAS 91-20-3)	Possible human carcinogen.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Naphthalene (CAS 91-20-3)	2B Possibly carcinogenic to humans.
<b>Toxic to reproduction</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity following single exposure</b>	May cause damage to organs. May cause respiratory irritation. May cause drowsiness and dizziness.
<b>Specific target organ toxicity following repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not likely, due to the form of the product.
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
<b>Bioaccumulation</b>	



P&WC

# SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

Version : 1.1

Date of preparation : 15 January 2018

Previous date : 09 January 2014

### Bioaccumulative potential

Octanol/water partition coefficient log Kow

Naphthalene 3.3

### Mobility in soil

No data available for this product.

### Other hazardous effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### Environmental fate

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

### Persistence and degradability

## 13. Disposal considerations

### Residual waste

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

### Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### Local disposal regulations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

## 14. Transport information

### CNDG

UN number

UN3082

UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (NAPHTHALENE, XYLENE)

Transport hazard class(es)

Class

9

Subsidiary risk

-

Packing group

III

### IATA

Not regulated as dangerous goods.

### IMDG

UN number

UN3082

UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (XYLENE, NAPHTHALENE)

Transport hazard class(es)

Class

9

Subsidiary risk

-

Packing group

III

Environmental hazards

Marine pollutant

No.

EmS

F-A, S-F

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established. Not applicable.

### CNDG







P&WC

# SAFETY DATA SHEET


## SPEC-AID 8Q5001 (FuelAid ULS 500)

Version : 1.1

Date of preparation : 15 January 2018

Previous date : 09 January 2014

IMDG



### 15. Regulatory information

#### Inventory of Existing Chemical Substances in China

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### Applicable regulations

OELs. Occupational Exposure Limits for Hazardous Agents in the Workplace, Part 1, Chemical Hazardous Agents  
 Law of the Peoples Republic of China on prevention of environmental pollution caused by solid waste  
 Provisions on the Environmental Administration of New Chemical substances  
 Rule of safety use the chemicals in workplace  
 List of Dangerous Goods  
 Classification and Labeling of Dangerous Chemical Substances Commonly Used  
 Safety Administration Regulations of the Hazardous Chemicals  
 National Catalogue of Hazardous Waste  
 Dangerous Chemical Products This safety data sheet conforms to the following laws, regulations and standards:  
 Regulations on the Control over Safety of Dangerous Chemicals  
 Regulations on Labor Protection in Workplaces Where Toxic Products Are Used  
 Measures for the Safe Use of Chemicals in Workplaces  
 Safety Data Sheet for Chemical Products - Content and Order of Sections (GB/T 16483-2008)  
 General Rules for Preparation of Precautionary Labels for Chemicals (GB15258-2009 )  
 Packing Symbol of Dangerous Goods(GB190-2009)  
 Packing - Pictorial Marking for Handling of Goods (GB/T191-2009)

#### General Rule For Classification and Hazard Communication of Chemicals (GB 13690-2009) and Catalog of Hazardous Chemicals

1,2,4-Trimethylbenzene (CAS 95-63-6)

Naphthalene (CAS 91-20-3)

#### Occupational exposure limits for hazardous agents in the workplace (GBZ 2.1-2007)

Naphthalene (CAS 91-20-3)

#### National Catalogue of Hazardous Wastes

Solvent naphtha (petroleum),heavy aromatic (CAS 64742-94-5)

#### List Of Priority Management of Hazardous Chemicals

Solvent naphtha (petroleum),heavy aromatic (CAS 64742-94-5)

#### Classification and code of dangerous goods (GB 6944-2012)

Regulated.

#### List of Dangerous Goods (GB 12268-2012)

Regulated.

#### The Principle of Classification of Transport Packaging Groups of Dangerous Goods (GB/T15098-2008)

Regulated.

#### General Specifications for Transport Packages of Dangerous Goods (GB 12463-2009)

Regulated.

#### Regulations on Road Transport of Dangerous Goods

Regulated.





P&WC

# SAFETY DATA SHEET

## SPEC-AID 8Q5001 (FuelAid ULS 500)

Version : 1.1

Date of preparation : 15 January 2018

Previous date : 09 January 2014

### Regulations on Rail Road Transport of Dangerous Goods

Regulated.

### UN Recommendations on the Transport of Dangerous Goods (UN RTDG)

Regulated.

## 16. Other information

### References

EPA: AQUIRE database  
GB6944-2012: Classification and Code of Dangerous Goods.  
GB12268-2012: List of Dangerous Goods.  
NLM: Hazardous Substances Data Base  
US. IARC Monographs on Occupational Exposures to Chemical Agents

### List of abbreviations

CAS: Chemical Abstract Service Registration Number  
ACGIH: American Conference of Governmental Industrial Hygienists  
NOEL: No Observed Effect Level  
STEL: Short Term Exposure Limit  
LC50: Lethal Concentration, 50%  
TWA: Time Weighted Average  
BOD: Biochemical Oxygen Demand  
COD: Chemical Oxygen Demand  
TOC: Total Organic Carbon  
LD50: Lethal Dose, 50%  
NFPA: National Fire Protection Association  
EC50: Effect Concentration, 50%  
CEN: European Committee for Standardisation

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### Revision information

This document has undergone significant changes and should be reviewed in its entirety.

\* Trademark of SUEZ. May be registered in one or more countries.